



## Ceiling and Wall Mount Occupancy Sensor

### *Ultrasonic Line Voltage Ceiling Mount Sensor*

#### KEY FEATURES

- Self-contained power supply
- 2,000 square-foot coverage
- Adjustable time delay
- Adjustable sensitivity
- UL and cUL listed
- 5-year warranty



C5002000P

#### OVERVIEW

The C5002000P uses ultrasonic (US) technology to turn lighting systems on and off based on occupancy. Designed specifically for areas where tasks consist of minor motion for long periods of time (e.g. typing), the C5002000P provides long-term trouble-free operations.

#### FEATURES and BENEFITS

Features	Benefits
Self-contained power supply	• Does not require Class 2 (low-voltage) wiring or a separate power pack
2,000 square-foot coverage	• Wide coverage area
Adjustable time delay and sensitivity	• Time delay: 30 seconds–30 minutes • Sensitivity: 0%–100%

#### APPLICATIONS

- Hallways
- Restrooms
- Storage facilities

## SPECIFICATIONS

Sensitivity	<ul style="list-style-type: none"><li>Fully adjustable: 0% –00%</li></ul>
Timer timeout	<ul style="list-style-type: none"><li>Fully adjustable: 30 seconds–30 minutes</li></ul>
Ultrasonic output	<ul style="list-style-type: none"><li>Operating frequency: 32.7kHz</li></ul>
LED lamp	<ul style="list-style-type: none"><li>Walk test indicator (a blinking light indicates the sensor is working)</li></ul>
Coverage	<ul style="list-style-type: none"><li>2,000 square feet</li></ul>
Power requirements	<ul style="list-style-type: none"><li>C5002000P120: 120 VAC; 50/60 Hz</li><li>C5002000P277: 277 VAC; 50/60 Hz</li></ul>
Electrical ratings	<ul style="list-style-type: none"><li>C5002000P120: 2400 watts @ 120 VAC; 50/60 Hz</li><li>C5002000P277: 5000 watts @ 277 VAC; 50/60 Hz</li></ul>
Operating environment	<ul style="list-style-type: none"><li>Indoor use only</li><li>Operating temperature: 32<sup>o</sup>–122<sup>o</sup>F (0<sup>o</sup>–50<sup>o</sup>C)</li></ul>
Construction	<ul style="list-style-type: none"><li>Casing—rugged, high-impact, injection-molded plastic</li><li>Color-coded leads</li></ul>
Size and weight	<ul style="list-style-type: none"><li>Size: 5.0" x 2.87" x 1.37" (127.5 mm x 73.0 mm x 35.0 mm)</li><li>Weight: 3.0 oz</li></ul>
Color	<ul style="list-style-type: none"><li>White</li></ul>
Mounting	<ul style="list-style-type: none"><li>Sensors can be mounted using a single-gang mud ring attached to a 4-inch square electrical box</li><li>Recommended MAX mounting height: 9ft.</li></ul>
Certifications	<ul style="list-style-type: none"><li>UL and cUL listed</li></ul>
Warranty	<ul style="list-style-type: none"><li>5 years</li></ul>

## HOW TO ORDER

Catalog Number	Description	Color	Coverage
C5002000P120	Ultrasonic Line Voltage Ceiling Mount Sensor, 120VAC	White	2000 sq. ft.
C5002000P277	Ultrasonic Line Voltage Ceiling Mount Sensor, 277VAC	White	2000 sq. ft.



**Building Automation, Inc.**

**Hubbell Building Automation, Inc.**  
9601 Dessau Road | Building One | Austin, Texas 78754  
{512} 450-1100 | {512} 450-1215 fax  
[hubbell-automation.com](http://hubbell-automation.com)