



Power Packs and Relays

Line Voltage Auxiliary Relays

KEY FEATURES

- 120 or 277VAC models available
- 20 Amp switching capacity
- N.O. isolated contact
- UL and cUL listed
- Five-year warranty



OVERVIEW

Hubbell Building Automation’s remote relay units (RRU) are used to switch additional lighting or other control circuits. Designed to work with line voltage sensors, the RRU provides 20 amp switching capacity and features a Normally Open (N.O.) isolated contact.

SPECIFICATIONS

Electrical Ratings	<ul style="list-style-type: none"> • RRU120 – 2400 watts @ 120 VAC 50/60 Hz, 1 HP • RRU277 – 5000 watts @ 277 VAC 50/60 Hz, 1.5 HP
Operating environment	<ul style="list-style-type: none"> • Indoor use only
Size & Weight	<ul style="list-style-type: none"> • Size: 2.75” W x 4.5” L x 1.10” D • Weight: 3.0 oz
Color	<ul style="list-style-type: none"> • White
Certifications	<ul style="list-style-type: none"> • UL and cUL Listed
Warranty	<ul style="list-style-type: none"> • 5 years

HOW TO ORDER

Catalog Number	Description
RRU120	Auxiliary Relay Unit For Use With Line Voltage Sensors, 120VAC 50/60Hz
RRU277	Auxiliary Relay Unit For Use With Line Voltage Sensors, 277VAC 50/60Hz